

The "No-Twist" Telescopic Rod is designed and manufactured by Hastings Fibreglass, the originators of Telescoping Hot Sticks.



The unique triangular design ensures the rods can be erected speedily whether being used for fusing, switching and tree cutting operations or to apply ropes to pole tops for use with "First Man Up" equipment. As standard the rods are supplied with the universal fitting and hook.

HV Range

TEL-O-POLE II, The No-Twist Stick

- Triangular shape - enables each section to lock in automatically. No twisting required to lock sections together
- High visibility - fluorescent top section is highly visible and has a foam core
- Extra reach - standard models reach to 30ft, 35ft or 40ft
- Shorter rods - designed for engineers to fit in smaller vehicles
- More versatile - use only the number of sections required to perform each job
- For reduced height simply depress the lock button and slide the bottom section off - this allows for a lightweight tool to perform the work task more easily
- Easy disassembly for cleaning and maintenance - no tools are required for disassembly
- Ergonomic design - allows the operator a more positive grip for greater control
- Easy maintenance - all sections have a smooth glossy surface for routine cleaning and waxing
- Dielectrically tested - each section is tested to 100kV per foot
- HV-208 only 27 inches long when retracted - excellent for use from bucket truck



Universal fitting head supplied as standard

Nylon head available upon request



Intermediate sections with large buttons for ease of use with or without gloves



Bottom section has rubber base cap which cushions and protects the fibreglass



HV-208

CAT NO	EXTENDED LENGTH	RETRACTED LENGTH	WEIGHT	NO. OF SECTIONS
HV-208	8' (2.43m)	27" (0.69m)	1.4kg	5
HV-220	21' (6.43m)	62" (1.58m)	2.92kg	5
HV-225	25' 6" (7.8m)	64" (1.63m)	3.68kg	6
HV-230	30' (9.14m)	66" (1.67m)	4.55kg	7
HV-230S	21' (6.4m)	52" (1.32m)	3.8kg	7
HV-235	35' (10.67m)	68" (1.72m)	5.5kg	8
HV-235S	25' (7.62m)	53" (1.34m)	4.85kg	8
HV-240	39' 6" (12m)	69" (1.75m)	6.5kg	9
HV-240S	29' (8.84m)	54" (1.37m)	5.78kg	9

For nylon head in place of universal head add 'SP' to catalogue number. eg HV-230-SP.

Accessories

CAT NO	DESCRIPTION
TEL-AD	Adapter to convert universal fitting to accept standard pole heads
B70X4RW2P	Storage bag with 2 pockets for HV-230, HV-235, HV-240 & MV Range
B56X4RW2P	Storage bag with 2 pockets for HV-230S, HV-235S & HV-240S



TEL-AD