



## MV Range

Triangular Operating Rod with Measurements



This heavy-duty operating rod features metric scale measurement graduations for eye-level reading. Graduations are silk-screen printed directly on the fibreglass sections and will not chip or peel. The surface is then re-coated with a hard, high-gloss epoxy finish. Measurements are printed in large, easy to read numerals.

The MV range enables users to operate switches and fuses, perform tree-cutting operations and measure heights and clearances.

Note: The MV range is a triangular "No-Twist" stick.

CAT NO	EXTENDED LENGTH	RETRACTED LENGTH	BASE DIAMETER	WEIGHT	NO. OF SECTIONS
<b>MV-25</b>	25' 7" (7.8m)	5' 4" (1.63m)	48.5mm	3.7kg	6
<b>MV-30</b>	30' 2" (9.2m)	5' 6" (1.68m)	52.5mm	4.5kg	7
<b>MV-35</b>	34' 9" (10.6m)	5' 7" (1.72m)	56mm	5.5kg	8
<b>MV-40</b>	39' 4" (12m)	5' 9" (1.75m)	60.4mm	6.5kg	9



## Accessories

CAT NO	DESCRIPTION
<b>B70X4RW2P</b>	Storage bag, 70" long, with 2 pockets for HV230, HV235, HV240, MV30, MV35, MV40, M35, M40, M50.
<b>B56X4RW2P</b>	Storage bag, 56" long, with 2 pockets for HV230S, HV235S, HV240S.



## M Range

Round Measuring Stick

The 'M' range of measuring sticks is ideal for fast and accurate measurements of overhead lines, structures, bridges and transport carriers.

- Lightweight construction and easy to use
- Measure heights up to 15m
- Eye level reading - no calculations required
- Positive locking buttons, spring-loaded, fast, accurate and easy to extend
- Plastic hook on tip section
- Large red printed graduations
- Storage bag available for all models

CAT NO	EXTENDED LENGTH	RETRACTED LENGTH	WEIGHT
<b>M-25</b>	24' 7" (7.5m)	5' 5" (1.67m)	1.45kg
<b>M-35</b>	34' 5" (10.5m)	5' 5" (1.67m)	2.66kg
<b>M-40</b>	39' 4" (12m)	5' 5" (1.67m)	3.4kg
<b>M-50</b>	49' 2" (15m)	5' 9" (1.76m)	6kg

