

## Myquip High Performance Wipes

**CAT NO: 68250**

Myquip High Performance Wipes are ideal for cleaning and degreasing equipment used for live working such as hot sticks, rubber blankets, linehose, insulator covers and vehicle fibreglass booms. Also used for cleaning bitumen and contaminants from underground cables. Supplied in sealed self contained tubs, these wipes are very convenient - simply pull out a fresh wipe when required. Each tub contains 250 wipes.



## Hot Stick Handguard

Moulded from non-conductive derlin, split sleeve design allows easy attachment to tool. Also designed for tools with operating rod.

CAT NO	DESCRIPTION
<b>A30002</b>	For use with a 1¼" (32mm) diameter pole
<b>A30003</b>	For use with a 1½" (38mm) diameter pole

## Urethane Hanger Hook

**CAT NO: 10-151-2**

Dielectric hook attaches onto hot sticks with jubilee clip.



## 'C' Assist

**CAT NO: A30152**

Attaches to tie wire sticks to assist binding and unbinding.



## Hot Stick Tester

Easy to apply tester is used for testing live line tools and switching rods. Can be used for "in service" testing to OSHA 1910.269. A selector switch is used for wet or dry test and a dual range scale which gives the operator leakage current values in microamps.

Utilising a 2500 volt output the meter is calibrated to indicate the leakage values that would be present if 75kVAC were applied to a 300mm section of fibreglass pole for the wet test and 100kVAC per 300mm for the dry test.

Portable and lightweight, the tester comes in 2 models for 120 volt and 220 volt systems. The tester is designed to protect the operator during use. Comes complete with padded carrying case and a testing bar which is provided to ensure the tester is working correctly.



CAT NO	DESCRIPTION
<b>6781</b>	Hot Stick Tester for 220V systems
<b>6799</b>	Hot Stick Tester for 110V systems