

Open Ended Spanners

Available in metric sizes 6mm to 36mm, imperial sizes ¼" to 1" A/F and Whitworth sizes 1/8"W to 1"W. The spanners are made of chrome vanadium steel, torque tested according to DIN 899 and feature professional multi-coated insulation.

Also available: Miniature BA Open Ended Spanners in sizes 0Ba, 2Ba, 3Ba and 4Ba.



Adjustable Spanners

The range is available in jaw opening sizes from 17mm to 60mm. The spanners are made of chrome vanadium steel with measurement scale on jaws to size nuts and pipes. Cross section of the knurl is tapered to give a smoother and more precise action. Professional multi coated insulation. Also available with hand stop.

Ring Spanners

Available in metric sizes 6mm to 36mm, imperial sizes ¼" to 1" A/F and Whitworth sizes 1/8"W to 1"W. The spanners are made of chrome vanadium steel and are suitable for live work up to 1000V. Conforms to ISO 10104, DIN 838 and UNE 16522.



Reversible Ratchet Lever

Manufactured of alloyed and hardened steel and featuring clockwise and anti-clockwise operation, the reversible ratchet lever's socket locking mechanism allows quick release. Professional multi coated insulation. Available in ¾" and ½" square drive.

Extension Bar

Manufactured of alloyed steel, the extension bar enables the socket to be secured by an expanding ball bearing. Suitable for all types of socket. Professional multi coated insulation.



Adjustable Torque Ratchet Wrench

Manufactured of alloyed and hardened steel. The socket is secured by an expanding ball bearing. Suitable for all types of screwdriver heads. Adjustment tolerance can be ± of the nominal value. Anti-clockwise operation without limitation. Professional multi coated insulation.

The range features sizes ¼" 'Mini', ½" and ¾" drive with adjustable torque from 2 - 250Nm.

Sockets - ¾" & ½" Square Drive

A full range of sockets are available in ¾" square drive - standard insulated sockets 6mm to 24mm, long sockets 8mm to 30mm (A/F and Whitworth also available). The ½" square drive sockets are available 8mm to 34mm, long sockets 8mm to 32mm (A/F and Whitworth also available).

All inserts are manufactured of alloyed and hardened steel, and the socket is secured by an expanding ball bearing.

