

All our insulated screwdriver blades are manufactured from precision hardened Chrome-Vanadium-Molybdenum steel, with a durable non-peel black finish. The blade insulation is directly moulded onto the blade.

The handles feature ergonomic, softgrip multi-component technology and a hanging hole. Individually tested in a water bath according to DIN EN 60900, IEC 900 norms.



1000V  
EN/IEC 60900:2004

## Slotted Screwdrivers

Available with tip width of 0.4mm to 1.6mm and blade length of 75mm to 200mm, high torque softgrip screwdrivers for slotted screws. Tips and dimensions according to DIN 7437, ISO 2380, DIN 5264.

## Hexagon Screwdrivers

Available with tip size to suit 3mm to 6mm hex, high torque softgrip screwdrivers for hexagon socket screws.



1000V  
EN/IEC 60900:2004



1000V  
EN/IEC 60900:2004

## Phillips Screwdrivers

Available with point size of PH0 to PH4, high torque softgrip screwdrivers for Phillips screws. Tips and dimensions according to DIN 7438, ISO 8764-PZ.

## Pozidrive Screwdrivers

Available with point size of PZ0 to PZ4, high torque softgrip screwdrivers for Pozidrive screws. Tips and dimensions according to DIN 7438, ISO 8764-PZ.



1000V  
EN/IEC 60900:2004



1000V  
EN/IEC 60900:2004

## Nut Spinner

Available with tip size to suit 4mm to 14mm hex, high torque softgrip screwdrivers for hexagon headed nuts, bolts and screws.

## Link Extractors

Link extractors are available in a range of sizes with male or female thread and a choice of straight or "T" handles.



1000V  
EN/IEC 60900:2004

Female Link Extractor



1000V  
EN/IEC 60900:2004

Male Link Extractor



1000V  
EN/IEC 60900:2004

Male 'T' Bar  
Link Extractor



Female 'T' Bar  
Link Extractor