

The Klauke Multi Tool has been designed to be versatile and, by accepting a range of adapters, enables the user to crimp, cut and punch with a single tool. Available in the mini+, ultra and ultra+ ranges for complete versatility. All models come with rotating, universal flip top head that accepts various crimping dies, cable cutting dies, Greenlee punching adapter, and special cutters for DIN rail and threaded bar. Has all of the features of the Klauke Safety Plus range.

Mini+ Multi Tool

Battery-powered tool with rotatable latch-type universal head. Adapters for crimping dies of the Klauke Series 5, 18 and 22. Various cutting dies for Al and Cu cables with and without armouring. Dies for cutting threaded rods and DIN rails are also available, in addition to a punching adapter for Greenlee punching tools and a range of punching dies.



CAT NO	EKM 60 UNV-L
FORCE	60kN
STROKE/OPENING WIDTH	27mm
CRIMP RANGE	6mm ² - 300mm ²
NUMBER OF CRIMPS	Approx 200 for 150mm ² Cu DIN
CUTTING RANGE	Max 25mm dia
CABLE TYPES	Armoured Cu & Al cable, ACSR
NUMBER OF CUTS	Approx 165-300
PUNCHING CAPACITY	Up to 64mm round holes in stainless steel; Up to 92 x 92mm square in mild steel
WEIGHT INC. BATTERY	3.0kg

UCACSR: Cutting dies for ACSR up to max 40mm dia



UC40: Cutting dies for Cu/Al cables up to 40mm dia

UCM*: Cutting dies for cutting threaded rods, metric M5 - M12



UCD3515: Cutting dies for DIN rails 35 x 15mm (other sizes available)

UA6P: Punching adapter for use with Greenlee sheet metal hole punching system



Ultra & Ultra+ Multi Tool

Battery-powered tool with rotatable latch-type universal head. Adapters for crimping dies of the Klauke Series 5, 18 and 22. Various cutting dies for Al and Cu cables with and without armouring. Dies for cutting threaded rods and DIN rails are also available, in addition to a punching adapter for Greenlee punching tools and a range of punching dies.

CAT NO	EK 60 UNV-L	EK 120 UNV-L
FORCE	60kN	108kN
CRIMP RANGE	6mm ² - 300mm ²	10mm ² - 400mm ²
NUMBER OF CRIMPS	Approx 300 for 150mm ² Cu DIN	Approx 110 for 150mm ² Cu DIN
CUTTING RANGE	Max 40mm dia	Max 40mm dia
NUMBER OF CUTS	Approx 110	Approx 110
PUNCHING CAPACITY	Up to 64mm dia round	Up to 144mm dia round Up to 138 x 138mm square
WEIGHT INC. BATTERY	4.6kg	6.3kg

