

Klauke Batteries



Features:

- For battery powered tools including Klauke mini, Klauke mini+, Klauke ultra, Klauke ultra+ and Klauke Multi series
- No memory - effect
- Extremely low self-discharge
- Lightweight



RAL2



RAM3



RA5

CAT NO	VOLTAGE	CAPACITY	CHARGING TIME	TECHNOLOGY	WEIGHT
RAL2	18V	3.0Ah	15 min with LGL1	Li-Ion	0.6kg
RAM3	9.6V	3.0Ah	40 / 15 min with LG4F / LG5	NiMH	0.5kg
RA5	12V	3.0Ah	40 / 15 min with LG4F / LG5	NiMH	0.6kg

Klauke Chargers & Mains Adapter

Horizon supplies a wide range of Klauke chargers. The mains adapter can be used with all Klauke Li-Ion tools.



CAT NO	LGL 1	LGL 2	LG 4F	LG 5	LG 6	NG2230
USAGE	Quick-charger for 18V Li-Ion batteries	12V car charger for 18V Li-Ion batteries	Charger for NiCd and NiMH batteries, 230V mains power	Quick charger for NiCd and NiMH batteries	12V car charger for NiCd and NiMH batteries	18V mains adapter for 115V or 230V voltage
CHARGE TIME	15 / 22 min with RAL1 / RAL2	30 / 60 min with RAL1 / RAL2	40 - 60 min	NiCd: 10 - 60 min, NiMH: 20 - 30 min	NiCd: 45 - 70 min, NiMH: 45-75 min	-
MAINS SUPPLY	230V AC	12V	230V AC	230V AC	12V DC	230V
VOLTAGE	18V	18V	7.2V / 9.6V / 12V / 14.4V DC	7.2V / 9.6V / 12V / 14.4V DC	7.2V / 9.6V / 12V / 14.4V DC	18V
WEIGHT	1.0kg	1.0kg	0.5kg	1.3kg	0.6kg	0.8kg