



## Klauke PK60VP

Hydraulic crimping head 10 - 240mm<sup>2</sup> for tubular cable lugs, standard type connectors, fine and superfine stranded conductors. Centring system for optimum crimping results. Quad point indent crimping. No dies required, wide crimping. Open crimping head with quick coupling, rotates 360°.



| CAT NO | CRIMPING RANGE          | CRIMPING FORCE | OPERATING PRESSURE | LENGTH | WEIGHT |
|--------|-------------------------|----------------|--------------------|--------|--------|
| PK60VP | 10 - 240mm <sup>2</sup> | 55kN           | Max 590bar         | 305mm  | 2.8kg  |



## Klauke PK120/42

Hydraulic crimping head 10 - 400mm<sup>2</sup> for use with industry-standard 'U' dies. C-head with 42mm opening width offers large crimping range. Up to 60% less crimping operations due to wide crimping (compared to 6-ton tools). Crimping head rotates 360°.

| CAT NO   | CRIMPING RANGE          | CRIMPING FORCE | OPERATING PRESSURE | LENGTH | WEIGHT |
|----------|-------------------------|----------------|--------------------|--------|--------|
| PK120/42 | 10 - 400mm <sup>2</sup> | 120kN          | Max 700bar         | 335mm  | 4.5kg  |

## Klauke PK25/2

Hydraulic crimping head 16 - 625mm<sup>2</sup> for use with Klauke Series 25 interchangeable dies. Very large crimping range. Head rotates 360°.

| CAT NO | CRIMPING RANGE          | CRIMPING FORCE | OPERATING PRESSURE | LENGTH | WEIGHT |
|--------|-------------------------|----------------|--------------------|--------|--------|
| PK25/2 | 16 - 625mm <sup>2</sup> | 250kN          | Max 700bar         | 335mm  | 5.3kg  |



## Klauke PK45

Heavy duty hydraulic crimping head 120 - 1,000mm<sup>2</sup> for use with Klauke Series 45 interchangeable dies. Very large crimping range. Crimping head rotates 360°.

| CAT NO | CRIMPING RANGE             | CRIMPING FORCE | OPERATING PRESSURE | LENGTH | WEIGHT |
|--------|----------------------------|----------------|--------------------|--------|--------|
| PK45   | 120 - 1,000mm <sup>2</sup> | 450kN          | Max 700bar         | 265mm  | 10.3kg |

## Klauke PK1000

Powerful hydraulic crimping head, 1000kN. Single acting crimping head for connecting to hydraulic drive units. Robust and compact design. For use with special interchangeable dies available on request.

| CAT NO | CRIMPING RANGE      | CRIMPING FORCE | OPERATING PRESSURE | WEIGHT |
|--------|---------------------|----------------|--------------------|--------|
| PK1000 | 1600mm <sup>2</sup> | 1000kN         | Max 700bar         | 27kg   |



For dies see page B18