



Klauke SDG45

Hydraulic cutting head 45mm diameter. Cuts armoured Cu and Al cables and ACSR. Closed head with bolt interlock, flip open jaws. Cutting head rotates 360°.

CAT NO	CUTTING RANGE	CUTTING FORCE	OPERATING PRESSURE	LENGTH	WEIGHT
SDG45	45mm dia	60kN	Max 700bar	340mm	3.8kg



Klauke SDG85/2

Hydraulic cutting head 85mm diameter. Cuts Cu and Al cable with light steel armour. Very low weight. Closed head with bolt interlock, flip top style. Cutting head rotates 360°.

CAT NO	CUTTING RANGE	CUTTING FORCE	OPERATING PRESSURE	LENGTH	WEIGHT
SDG85/2	85mm dia	60kN	Max 700bar	445mm	4.3kg

Klauke SDG105

Hydraulic cutting head 105mm diameter. Cuts armoured Cu and Al cables. Closed head with bolt interlock. Cutting head rotates 360°.

CAT NO	CUTTING RANGE	CUTTING FORCE	OPERATING PRESSURE	LENGTH	WEIGHT
SDG105	105mm dia	120kN	Max 700bar	432mm	7.7kg



Klauke SDK65

Hydraulic cutting head 65mm diameter. Cuts Cu and Al cable with light steel armour. Open cutting head. Cutting head rotates 360°.

CAT NO	CUTTING RANGE	CUTTING FORCE	OPERATING PRESSURE	LENGTH	WEIGHT
SDK65	65mm dia	42kN	Max 700bar	425mm	4.7kg

Klauke SDK120

Hydraulic cutting head 120mm diameter. Very wide cutting range. Cuts Cu and Al cable with light steel armour. Open cutting head. Cutting head rotates 360°.

CAT NO	CUTTING RANGE	CUTTING FORCE	OPERATING PRESSURE	LENGTH	WEIGHT
SDK120	120mm dia	55kN	Max 700bar	538mm	8.7kg

