



Y35


Hand hydraulic crimping tool for use on Cu & Al terminals. Crimping head rotates 360°. Rapid ram advance. Also available with insulated head (Y35/2). Accepts industry standard 'U' dies.

CAT NO	CRIMPING FORCE	OPERATING PRESSURE	LENGTH	WEIGHT
Y35	120kN	700bar (10,000psi)	575mm	6kg
Y35/2		As Y35 but with insulated head		6.5kg

Y35BH

Remote crimping head for use on Cu & Al terminals. Accepts industry standard 'U' dies. Head adapter available for use with universal tool for live working applications.

CAT NO	CRIMPING FORCE	OPERATING PRESSURE	WEIGHT
Y35BH	120kN	700bar (10,000psi)	3kg
ADP070		Head adapter for Y35BH crimping head	



G10TS

Hand hydraulic crimping tool for use on 10mm² to 400mm² (Cu) and up to 300mm² (Al). Two stage operation with insulated body and handles. Preset overload valve ensures crimp reliability. Accepts industry standard 'U' dies.

CAT NO	CRIMPING FORCE	OPERATING PRESSURE	LENGTH	WEIGHT
G10TS	115kN	700bar (10,000psi)	485mm	6.2kg

Hydraulic Cutters

Lightweight portable robust hydraulic cutter with guillotine type cutting head which rotates 180 degrees. Flip top latch head allows easy positioning onto the conductor. Blades are easy to replace. Tool comes in soft carry case.

CAT NO	CAPACITY	LENGTH	WEIGHT
S-20A	ACSR 20mm dia / Stay Wire 16mm dia	390mm	2.8kg
S-24	ACSR 24mm dia / Stay Wire 20mm dia	430mm	4.0kg



For dies see page B18