

Heavy Duty Cable Stockings

For use on Underground Cable & Overhead Lines

These stockings are heavy duty, triple weave, single flexible eye with shoulders.



| CAT NO | RANGE | LENGTH | MIN BREAKING STRENGTH |
|-----------|-----------|--------|-----------------------|
| E858-0631 | 6 - 13mm | 650mm | 2250kg |
| E858-1231 | 12 - 19mm | 825mm | 3380kg |
| E858-1931 | 19 - 25mm | 1025mm | 5540kg |
| E858-2531 | 25 - 32mm | 1300mm | 9550kg |
| E858-3231 | 32 - 38mm | 1400mm | 11,456kg |

Non-Conductive Cable Stockings for ABC/ Insulated Cable



Manufactured from high strength parallel standard fibre with polyethylene sheath, these stockings are non-conductive, non-corrosive and abrasive resistant.

Available in single or double weave. Sizes listed are single eye, double eye available on request.

| CAT NO | SINGLE / DOUBLE | RANGE | LENGTH | MIN BREAKING STRENGTH |
|-----------|-----------------|--|--------|-----------------------|
| E677-1011 | Single | 10 - 20mm (2 x 25mm ²) | 600mm | 1120kg |
| E677-2011 | Single | 20 - 30mm (2 x 35 - 70mm ² & 4 x 25 - 50mm ²) | 600mm | 1680kg |
| E677-3011 | Single | 30 - 40mm (2 x 95mm ² & 4 x 70 - 95mm ²) | 600mm | 2240kg |
| E677-3021 | Double | 30 - 40mm (2 x 95mm ² & 4 x 70 - 95mm ²) | 600mm | 4480kg |
| E677-4021 | Double | 40 - 50mm (4 x 1200mm ²) | 600mm | 5376kg |

General Duty Cable Stockings

For use on Underground Cable & Overhead Lines

General duty cable stockings available with single or double flexible pulling eye.



| SINGLE EYE CAT NO | DOUBLE EYE CAT NO | RANGE | LENGTH | MIN BREAKING STRENGTH |
|-------------------|-------------------|------------|--------|-----------------------|
| E546-0621 | E546-0622 | 6 - 13mm | 600mm | 1504kg |
| E546-1021 | E546-1022 | 10 - 20mm | 600mm | 1860kg |
| E546-2021 | E546-2022 | 20 - 30mm | 600mm | 2256kg |
| E546-3021 | E546-3022 | 30 - 40mm | 600mm | 3696kg |
| E546-4021 | E546-4022 | 40 - 50mm | 600mm | 5490kg |
| E546-5021 | E546-5022 | 50 - 65mm | 600mm | 5490kg |
| E546-6521 | E546-6522 | 65 - 80mm | 600mm | 7320kg |
| E546-8021 | E546-8022 | 80 - 95mm | 600mm | 7320kg |
| E546-9521 | E546-9522 | 95 - 110mm | 600mm | 10,613kg |

Swivels

Plated Finish

Swivels are fitted with bearings to prevent twisting during cable pulling operations. Precision manufactured in high grade steel with a plated finish.



| CAT NO | SWL | DIAMETER | LENGTH | JAW OPENING | PIN DIAMETER | WEIGHT |
|--------|--------|----------|--------|-------------|--------------|--------|
| 516 | 800kg | 26mm | 105mm | 10mm | 8mm | 0.26kg |
| 565 | 1600kg | 34mm | 108mm | 15mm | 10mm | 0.55kg |
| 564 | 3500kg | 37mm | 135mm | 15mm | 12.7mm | 0.75kg |
| 801 | 4500kg | 40mm | 142mm | 15mm | 14mm | 0.85kg |