

## Single Aluminium Sheave Suspension Blocks

Block has spring loaded safety gate and steel zinc plated frames. Choice of swivel oval eye or tongue mounting with hole to fit clevis. The sheave has a groove width of 45mm, with an internal diameter of 245mm and an outside diameter of 300mm. Neoprene groove lining available on request.

CAT NO	DESCRIPTION	SWL	WEIGHT
D-691-010	Suspension block with oval eye	1200kg	9.0kg
D-691-020	Suspension block with tongue mounting	1200kg	9.0kg

Large suspension block with oval eye



Suspension block with tongue mounting



Suspension block with oval eye

## Large Single Aluminium Sheave Suspension Blocks

Larger diameter sheave with higher safe working load. Block has spring loaded safety gate and steel zinc plated frames. Choice of swivel oval eye or tongue mounting with hole to fit clevis. The sheave has a groove width of 45mm, with an internal diameter of 385mm and an outside diameter of 470mm. Neoprene groove lining available on request.

CAT NO	DESCRIPTION	SWL	WEIGHT
D-700-010	Suspension block with oval eye	2400kg	14.0kg
D-700-020	Suspension block with tongue mounting	2400kg	14.0kg

## Swivel Sagging Block

Designed to fit tower cross arm to accept wire rope for sagging conductor. Each block will accept a maximum wire rope diameter of 24mm.

CAT NO	DESCRIPTION	SWL	MAX BOLT SIZE
D-668-01	Swivel Sagging Block	1000kg	M16
D-668	Swivel Sagging Block	1750kg	M20
D-668-02	Swivel Sagging Block	2500kg	M22

