

## Harken Utility Snatch Blocks

Small, Lightweight, CE Snatch Block

Harken Snatch blocks are the workhorse for temporary rigging of rope for loads up to 500kg. The opening sideplates and simple operation make these compact blocks extremely versatile, allowing them to be quickly secured wherever needed. They are ideal for endless line operation; along with Working at Height and Confined Space rigging operations. It is a versatile block, ergonomic in construction, lightweight and can be used in many applications. This block is also fully CE Compliant.



CAT NO	DESCRIPTION	SWL	WEIGHT
443.1609E-H	Utility Snatch Block, Side Opening, with Swivel Hook & Gate	500kg	1.05kg
443.1609E-SH	Utility Snatch Block, Side Opening, with Double Action Scaffold Karabiner	500kg	1.25kg
443.1609E	Utility Snatch Block, Side Opening, with Swivel Eye	500kg	0.5kg



## McKissick Blocks

Steel Snatch Blocks

High quality steel snatch blocks fitted with choice of swivel hook or shackle. Forged alloy heat treated hooks, yokes and shackles. Pressure lube fittings, fatigue rated.

CAT NO	SHEAVE DIAMETER	FITTING	WIRE ROPE SIZE	SWL	WEIGHT
BB-108038	3" (76mm)	Swivel Hook	8 - 10mm	2000kg	2.04kg
BB-109037	3" (76mm)	Shackle	8 - 10mm	2000kg	1.81kg
BB-108065	4.5" (114mm)	Swivel Hook	10 - 13mm	4000kg	5.31kg
BB-109064	4.5" (114mm)	Shackle	10 - 13mm	4000kg	5.44kg
BB-108127	6" (152mm)	Swivel Hook	16 - 19mm	8000kg	12.2kg
BB-109126	6" (152mm)	Shackle	16 - 19mm	8000kg	12.6kg
BB-108323	10" (254mm)	Swivel Hook	16 - 19mm	8000kg	18.6kg
BB-109322	10" (254mm)	Shackle	16 - 19mm	8000kg	19.1kg

## Steel Snatch Block

Steel snatch blocks are available with safe working loads from 0.5 to 6 tonnes. These blocks have bushed sheaves and are suitable for use with wire rope, conductor or nylon rope. The blocks have a swivel hook and safety catch.

CAT NO	SHEAVE DIAMETER	SWL	WEIGHT	CAT NO	SHEAVE DIAMETER	SWL	WEIGHT
SNBH075	3" (76mm)	500kg	1.7kg	SNBH175	7" (178mm)	3000kg	12kg
SNBH100	4" (102mm)	1000kg	3.2kg	SNBH200	8" (203mm)	4000kg	18kg
SNBH125	5" (127mm)	1500kg	5kg	SNBH250	10" (252mm)	5000kg	27kg
SNBH150	6" (152mm)	2000kg	8kg	SNBH300	12" (305mm)	6000kg	40kg

