

Round Slings



Nylon round slings are offered in a range of sizes and capacities. Universal colour coding ensures correct safe working load. Manufactured from high quality polyester, these heavy duty slings are ideal for a harsh working environment. All slings are supplied with a certificate of conformity.



Working load limit for each sling in basic configuration	Colour Coding	Available lengths circumference	Straight Pull M* = 1	Choke Hitch M* = 0.8	Basket Hitch Parallel M* = 2	Basket Hitch 90° M* = 1.4	Two Leg Sling Max 90° M* = 1.4	4 Leg Sling Max 90° M* = 2
1.0	Violet	1 to 32 metres	1.0	0.8	2.0	1.4	1.4	2.0
2.0	Green	1 to 32 metres	2.0	1.6	4.0	2.8	2.8	4.0
3.0	Yellow	1 to 32 metres	3.0	2.4	6.0	4.2	4.2	6.0
4.0	Grey	1 to 32 metres	4.0	3.2	8.0	5.6	5.6	8.0
5.0	Red	1 to 32 metres	5.0	4.0	10.0	7.0	7.0	10.0
6.0	Brown	2 to 32 metres	6.0	4.8	12.0	8.4	8.4	12.0
8.0	Blue	2 to 32 metres	8.0	6.4	16.0	11.2	11.2	16.0
10.0	Orange	2 to 32 metres	10.0	8.0	20.0	14.0	14.0	20.0

M = Mode Factor

Factor of safety for all webbing slings = 7 : 1

Working Load Limit (wLL) = Sling Rating x Mode Factor

Duplex Slings

Duplex slings are flat woven polyester with a becket eye at each end. Available in a range of sizes and capacities, they are colour coded to ensure that the correct sling is selected. Supplied with certificate of conformity.

Duplex slings are available in lengths: 1m, 2m, 3m, 4m, 5m, 6m, 8m and 10m.



Colour	Violet	Green	Yellow	Grey	Red	Brown	Blue
SWL	1000kg	2000kg	3000kg	4000kg	5000kg	6000kg	8000kg
Width	30mm	60mm	90mm	120mm	150mm	180mm	240mm