

Tsurumi Electric Submersible Trash Pump

CAT NO: HS2.4S-62 & HS3.75S

The HS series of Tsurumi Pumps are single phase, available in 230V or 110V versions. The pumps feature a shaft mounted agitator that handles solids up to 1" diameter and is capable of discharging up to 310 litres per minute.

Two models are available – the HS2.4S-62 with 50mm outlet and the larger HS3.75S with 80mm outlet offering increased head and flow capability. Both models are available as either standard operation or automatic with additional float switch.

These pumps have a solid cast aluminium body, cast iron pump casing and an impact resistant PVC strainer base for durability during robust handling.

50mm lay flat discharge hose in lengths of 10 to 50 metres supplied separately.



JCB Hydraulic Submersible Pump

JCB offers two clear water submersible pumps to suit two different hydraulic flow power packs. Hydraulically driven, and with high power to weight ratios, they are self lubricating and manufactured from aluminium – making them lightweight and corrosion free for life. Supplied with 10m hose (5cm diameter).



CAT NO	DISCHARGE PORT	HYD FLOW RANGE	MAXIMUM DISCHARGE	MAXIMUM HEAD	MAX OPERATING PRESSURE	WIDTH x HEIGHT	WEIGHT
929/03900	50mm	0-22 lpm	700 lpm	18m	138bar	230 x 302mm	8.2kg
929/04500	50mm	0-32 lpm	820 lpm	18m	138bar	230 x 302mm	8.5kg

SIP Water Pump

Powerful 5.5HP petrol driven engine, cast iron impeller and volute. Delivers a massive 600 litres per minute pumping capacity. 26 metre pumping head. 2" (50mm) inlet and outlet apertures. Built inside a robust protective frame. Suction and discharge hoses supplied separately.



CAT NO	DISCHARGE PORT	MAXIMUM DISCHARGE	MAXIMUM HEAD	WEIGHT
03924	50mm	600 lpm	26m	24kg



Honda Compact Water Pump

Self priming, 1.5HP 4-stroke, lightweight overhead Honda engine has recoil start and excellent pumping performance. Very fuel efficient, high quality aluminium pump body and mechanical seal. Maximum headlift 36m and 8m suction headlift. Includes butterfly couplers, hose clamps and plastic strainer.

CAT NO	DISCHARGE PORT	MAXIMUM DISCHARGE	MAXIMUM HEAD	WEIGHT
WX10	25mm	140 lpm	36m	6kg