

Deep Impact Sockets

Regular 6 point deep impact sockets, $\frac{3}{8}$ ", $\frac{1}{2}$ " and $\frac{3}{4}$ " square drive manufactured to DIN standard from chrome molybdenum for industrial use. The ranges covers metric, imperial and Whitworth sizes.



Stanley MicroTough Socket Set 29 Piece $\frac{1}{2}$ " Drive

Micro tough professional ratchet features a quick release two way ratchet with a 20-30% smaller pear shaped head, smaller than conventional ratchets for easy access in tight spaces. Fine tooth ratchet gives 5° angle of engagement – smoother operation and continues to function even where access to fastener is very restricted. Fully polished chrome plated finish for durability and rust resistance. Hex sockets feature Maxi Drive wall profile for improved grip on fastener. DynaGrip bi-material handle for comfortable grip.

The set consists of:

- 22 x $\frac{1}{2}$ " Bi-Hex sockets 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 23, 24, 26, 28, 29, 30 & 32mm
- 3 x $\frac{1}{2}$ " Extension bars 75mm (3"), 150mm (6") and 250mm (10")
- 1 x $\frac{1}{2}$ " Sliding T-bar
- 1 x $\frac{1}{2}$ " Universal joint
- 1 x $\frac{1}{2}$ " Reversible ratchet MicroTough
- 1 x $\frac{1}{2}$ " to $\frac{3}{8}$ " Adapter

Stubby Ratchet Spanner Set 7 Piece Metric

The Britool BRIE111104B 7 piece short ratchet ring wrench set is forged in chrome vanadium steel with a high chrome finish. The short wrenches allow better accessibility in confined spaces and have a 5° increment. The 12-point polygon head is angled at 15° and the open end is angled at 15° from the handle axis. The profile maximises the contact surface with the nut for a longer lifetime.

This set is supplied on a plastic storage rack and includes the following wrenches: 10, 12, 13, 14, 15, 17 and 19mm.



Combination Spanner Set 8 Piece 8 - 22mm

Maxi Drive Plus is a uniquely shaped jaw that locks the spanner onto the nut. Locking applies to the faces of the nut, thus preventing the risk of slipping. A high quality metric combination spanner made from chrome vanadium steel which conforms to ISO3318 DIN3313.

Supplied as a set of the following 8 sizes: 8, 10, 11, 13, 14, 15, 17 and 22mm.

Hammer Head Wrench

CAT NO: 10-312

Hammer head wrench with slip fit foam rubber grip handle. Jaw opens to 44mm (1 $\frac{3}{4}$ ") wide. Wrench is 300mm (12") long.

