

Sievert Promatic Universal Torch System

Promatic handle and Piezo ignition with instant trigger handle. Bayonet fitting for burners and double moulded soft grip for the highest comfort and usability. Valve for precise flame setting. Working pressure 1.5 - 4 bar. Weight 290g. Length 180mm.

Featuring automatic ignition guaranteed for 30,000 ignitions, trigger on/off function ensures no waste of LP gas, quick change bayonet fitted burners and swivel hose nipple to avoid hose drag. Load relieving trigger system, ergonomic and modern design, works in all weather conditions, wide range of burners for all applications.



Soft Flame Burners

Soft Flame Burners are ideal for cable work and other heat shrinking applications. Powerful yellow and blue soot free flames heat the sleeves efficiently but soft enough not to overheat the shrink material. Other sizes available on request.



CAT NO	DESCRIPTION
S334791	28mm diameter
S334191	38mm diameter
S334891	50mm diameter

Hot Air Burners

Hot Air burners with powerful windproof hot-air streams for heat shrinking. Ideal for shrinking in confined spaces.

CAT NO	DESCRIPTION
S333401	38mm diameter
S334990	32 x 15mm diameter
S335990	25mm diameter



Hoses

Standard hoses are available in 5mm, 6.3mm or 8mm diameters and can be supplied as factory fitted and leak tested hose kits. Hose length can be made to customer requirements.



Piezo Crystal Gas Igniter

CAT NO: 26-045

For use with butane or propane. 7" long.

Piezo ignition consists of a small, spring-loaded hammer which strikes a crystal of PZT or quartz crystal. Quartz is piezoelectric, which means that it creates a voltage when deformed. This sudden forceful deformation produces a high voltage and subsequent electrical discharge, which ignites the gas.