

A high quality fibreglass rod, specially constructed to provide exceptionally high tensile strengths, whilst retaining flexibility. The glass fibre core is reinforced with a high strength resin.

A braided reinforcing wrap is added before the final polypropylene wear resistant protective coating is applied. The continuous rods range from 4.5mm – 14mm diameter with lengths from 30 metres – 300 metres. Available in 4.5mm and 6.7mm diameter as standard and 9mm, 11mm and 14mm on request. A range of accessories is available including male and female threaded ferrules, tapered rod ends, flexible rod ends, pulling eyes and shackles.

Mini Rod 4.5mm

CASSETTE DIAMETER	REEL DIMENSIONS (LENGTH x WIDTH x HEIGHT)		MIN BEND RADIUS	BREAKING STRENGTH	
400mm	400 x 162 x 520mm		140mm	770kg	
CAT NO	B-101-030	B-101-050	B-101-060	B-101-070	B-101-080
LENGTH	30m	50m	60m	70m	80m
WEIGHT	4.5kg	4.8kg	5.0kg	5.3kg	5.5kg

Midi Rod 6.5mm

CASSETTE DIAMETER	REEL DIMENSIONS (LENGTH x WIDTH x HEIGHT)		MIN BEND RADIUS	BREAKING STRENGTH	
600mm	600 x 210 x 730mm		250mm	2500kg	
CAT NO	B-102-060	B-102-080	B-102-100	B-102-150	
LENGTH	60m	80m	100m	150m	
WEIGHT	9kg	10kg	11kg	13kg	



Speedy Spinner

3mm diameter fibreglass duct rod is uniquely designed in an impact resistant ABS housing for easy storage and practical handling. The spring loaded operation enables friction-free quick winding and unwinding of the rod.

Supplied with a range of accessories housed in the casing including: pulling grips, tape leaders and a repair glue kit for repairing 3mm fibreglass rods. 3 lengths available.

CAT NO	52055298	52055299	52055300
LENGTH	20m	30m	40m



Flexi Spinner

Featuring the same rugged ABS casing and spring loaded winding and unwinding facility as the Speedy Spinner but with 4.5mm diameter 3-fold twisted polyester tape which has 50% less friction than nylon and perlon. It is more suitable for long distances with narrow bending radiuses. 3 lengths available.

CAT NO	52055389	52055390	52055391
LENGTH	20m	25m	30m