


2-in-1 Head Torch

Dual function LED hand torch and head torch kit. Ultra compact and high powered, the torch has 4 mode functions: high, low, flashing and SOS. Unique 90° angled light and integrated clip on attachment. Operates from a single AA battery (included), head torch bracket, strap and battery.



CAT NO	LIGHT OUTPUT	LIGHT SOURCE	BEAM DISTANCE	RUN TIME	BATTERY	WEIGHT
2-IN-1	85 lumens	XP-E Cree LED	70m (high)	1h (high)	1 x AA	62g (inc battery)



HT290 LED Head Torch

Using a XP-G LED, deep dish reflector and thermal control technology, the HT290 is designed for optimum light output over a long distance. Using a multimode switch set to the side, allowing the user easy access (even with gloves) between the 4 light mode options (high, medium, low and SOS). The head is also compatible with larger battery belt packs which are suitable for when longer running times are required. Accessories include battery attachment case (bike/belt), battery belt packs, nylon pouch, extension cord and helmet clips.

CAT NO	LIGHT OUTPUT	LIGHT SOURCE	BEAM DISTANCE	RUN TIME	BATTERY	WEIGHT
HT290	290 lumens	XP-G Cree® LED	280m (high)	3½h (high)	4.8V 2.2Ah NiMH	352g

HT200 LED Head Torch

Using a XP-G LED, deep dish reflector and thermal control technology, the HT200 is designed for optimum light output over a long distance. Using a multimode switch set to the side, allowing the user ease of access (even with gloves) between the 4 light mode options (high, medium, low and SOS). Accessories include battery attachment case (bike/belt), battery belt packs, nylon pouch, extension cord and helmet clips.



CAT NO	LIGHT OUTPUT	LIGHT SOURCE	BEAM DISTANCE	RUN TIME	BATTERY	WEIGHT
HT200	200 lumens	XP-G Cree® LED	280m (high)	8h (high)	4 x AA	334g



HT070 LED Head Torch

Powered by 3 x AAA batteries (included), this lightweight and compact headtorch is very robust. The high power CREE XPC LED gives 70 lumens and a spot to flood beam using the built in optical diffuser, ideal for long distance and close up work. 5 light modes including high, low, strobe and red led for versatile applications. There are also two red LEDs which operate on the strobe and static settings for hazard warning and covert situations.

CAT NO	LIGHT OUTPUT (HIGH / LOW)	LIGHT SOURCE	RUN TIME (HIGH / LOW)	BATTERY	WEIGHT
HT070	70 / 17 lumens	Cree XPC LED	5h / 20h	3 x AAA	150g