

The TeleTower is an exciting and innovative product developed for the access industry. Its unique patented telescopic operation means it is easy to transport, store and erect. The TeleTower offers an efficient and lower-cost alternative to other low level access platforms.

Providing a working height of 4 metres, it is easily unloaded from a van and erected in 3 minutes or less!

Available in all aluminium or with fibreglass uprights for safer working near electrical hazards.

- Telescopic mechanism allows 5 adjustable platform heights from 1m to 2m (working heights from 3m to 4m)
- Operates as a podium with low level fixed height options of 33cm and 61cm
- Fully erected in under 3 minutes saving down time and man hours
- Can be transported in a small van or estate car
- Comprises only two parts – tower and platform
- Available in aluminium and GRP (non conductive)
- Large folding aluminium work platform (1.4m x 0.7m) with climb through hatch
- Integral telescopic hand and knee rails
- Integral platform stabilisers
- Integral stabilising legs with 5 optional positions
- Lockable castors
- Single person operation
- Minimal product footprint for ease of transportation and storage
- Optional toe - boards
- Conforms to EN1004
- Includes tower (33kg), platform (14kg), wheel set (8kg)



MAXIMUM LOAD	150kg
WEIGHT OF MAIN ASSEMBLY	41kg
WEIGHT OF PLATFORM	14kg
TOTAL WEIGHT	55kg
WEIGHT	36kg
PLATFORM HEIGHT (OPTIONS)	330mm, 610mm, 1m, 1.25m, 1.5m, 1.75m, 2m
FULLY COLLAPSED DIMENSIONS	1.1m x 0.8m x 0.45m with castors fitted (approx)
PLATFORM HEIGHT	
- 2.0m	2.94m (H) x 1.5m (W) x 0.92m (D)
- 1.75m	2.69m (H) x 1.5m (W) x 0.92m (D)
- 1.5m	2.44m (H) x 1.5m (W) x 0.92m (D)
- 1.25m	2.19m (H) x 1.5m (W) x 0.92m (D)
- 1.0m	1.94m (H) x 1.5m (W) x 0.92m (D)
- 610mm	1.46m (H) x 1.5m (W) x 0.92m (D)
- 330mm	1.46m (H) x 1.5m (W) x 0.92m (D)
CONSTRUCTION	Aluminium or Fibreglass
STANDARD	Conforms to EN1004



Find videos and additional resources for this product at www.horizonutilitysupplies.com