

SALA Pole Choke MkII

Designed to meet EA specification 43-123 and 43-124 and has passed the requirements for category A & B devices. The principle of the device is to arrest a fall by quickly choking around a wood pole to limit the fall distance, should the user fall whilst ascending or descending a pole or whilst in the work position. The pole choke is used with the SALA pole strap KF70126-B (shown separately below). It is designed for use on poles ranging from 5½" to 16" diameter. A pair of add on gaffs is incorporated into the choke kit and should be used where it is deemed the pole is unusually hazardous because of ice, algae or moss.



SALA Webbing Pole Strap



Designed for linesmen climbing wood poles. The KF70126-B is a pole strap / work-positioning device which is clipped to the side 'D's of a harness or work-positioning belt. The adjuster is easy to use one-handed even under tension. A PVC stiffener at the karabiner end allows the strap to be easily passed around the pole before clipping on to the harness 'D' ring.

CAT NO	MATERIAL	FITTINGS
KF70126-B	Polyester webbing	Twist-lock karabiner one end, screwgate tri 'D' other end

Trigger Work Positioning Lanyard

2m maximum length positioning lanyard utilises cam adjustment for length and locking into place. Features 11mm kernmantle rope with rope protector, twist-lock karabiner with 21mm opening at one end and 21mm snap-hook at the other end.



CAT NO	DESCRIPTION
KF7T2000	Trigger Positioning Lanyard

Protecta® Pro 2 Work Positioning Belt



A comfortable and lightweight work positioning belt which is equipped with many equipment loops and accessory holders. A very practical belt for safely storing tools. It can be used with any positioning lanyard in the PRO range.

CAT NO	AB051362	AB051336	AB051346
SIZE	Small	Medium / Large	Extra Large