

## Protecta® Anchorage Connector

Easy-to-fit rope operated anchorage connector for use with telescopic poles. The aluminium connector features a 60mm opening to suit scaffolding tubes. An adapter (supplied separately) must be used with telescopic/operating poles. Weight 1.05kg.



CAT NO	DESCRIPTION
2100105	Snap hook type anchorage connector



## Crochevit Jiraf

CAT NO: 1002899

Easy to install - the large opening is ideal for anchorage to girders and beams. High breaking strength in excess of 22kN. Used with a telescopic pole. The aluminium connector has an opening of 150mm dia (or 120 x 120mm square structure). Weight 1.32kg.

## DBI-SALA® Manucroche Hook

An anchor clamp in stainless steel wire, the Manucroche is the ideal connector for anchoring a fall arrest system to a steel structure. Its double locking system guarantees a connection that will withstand any fall.



CAT NO	AJ301	AJ302	AJ303
DESCRIPTION	75mm Manucroche Hook	110mm Manucroche Hook	140mm Manucroche Hook

## Girder Sling

The Ridgegear Girder sling is a quick and convenient way to attach fall arrest equipment to objects too large for a standard scaffold hook attachment method. Can also be used for attaching rescue equipment and secondary back up systems. This product is supplied in 1m, 2m and 4m lengths as standard.



RGK26



## DBI-SALA® Adjustable Width Trolley Anchor

This trolley is designed for use with self-retracting lifelines on horizontal beams and has been engineered for ease of use and superior performance. Glides effortlessly along the beam and provides horizontal mobility. Attachable anywhere along the beam, including the mid-point. Non-corrosive double-shielded wheel bearings are maintenance free. Trolley guards protect the wheels from damage and keep beam clear of debris.

CAT NO	DESCRIPTION
2103148	Adjustable Width Trolley Anchor

## Protecta® PRO-Line™ Temporary Lifeline

Portable, versatile and quick to install. A simple ratchet handle is used to tension the lifeline. No separate components, just connect to a suitable anchorage point. Lightweight and easy to handle, all components are incorporated into an integral carry bag. Built in shock absorber reduces end loadings to preserve the structure.



CAT NO	FEATURES
1200106	10m span, 8.8m fall clearance, 16kN end load
1200107	20m span, 11.02m fall clearance, 16kN end load