


## DBI-SALA® Mobi-Lok™ Industry Vacuum Anchor

Provides an anchorage on virtually any smooth, non-porous surface simply by flipping a switch and waiting for the green light. Lightweight design (under 10kg) for easy transport. Fail-safe back-up systems with audio alarms and vacuum level indicator. Rubber seals secure anchor without damaging surface. Can be used with horizontal lifeline systems for added mobility for up to four workers by joining two vacuum anchors together.



## DBI-SALA® Free Standing Counterweight

Free standing counterweight anchor which is easily placed on top of the roof surface to provide an anchorage for one worker. Includes 16 x 20.3kg cast iron weights, base plate, post and 'D' ring. Ideal where other anchorages are impractical.

CAT NO	DESCRIPTION
7255003	Free Standing Counterweight



## DBI-SALA® Uni Anchor Fall Arrest Post

Designed for use in sub-stations where finding an appropriately positioned fixed anchorage is impossible, the 14' Uni Anchor Fall Arrest Post provides an ideal option. It mounts using Uni-Anchor plates and extends up to 14' (4.2m) to provide a 1-man-rated fall-arrest anchor point.

The 14" (356mm) Anchor Post Extension allows for tie-off of one worker at an increased height of 68.5" (1740mm).


Accessories include:

- Weld-on Mounting Plate - unplated mild steel construction
- Uni-Anchor I-Beam Base - for connecting the PFAS to an I-Beam

CAT NO	DESCRIPTION
8516996	Uni Anchor Fall Arrest Post



Weld On Mounting Plate



Uni Anchor I-Beam Base

