

Horizon offers a range of solutions by Leading Edge for securing tools and equipment to ensure that they are held safely by the worker or secured closely in the work area. When working at height, both the law and common sense dictate that lanyards should be used to secure all hand tools from falling. The law specifically requires all personnel working at height to use such lanyards in addition to the fall arrest system to protect the worker. Most importantly, any tool dropped from height can become a deadly projectile if it lands on someone below. However, even without this danger, it is unproductive to have to retrieve fallen tools.



## Elasticated Tool Lanyards

Elasticated tool lanyards are a premium safety tool lanyard. The design provides flexibility in reach, combined with durability via a tubular protective webbing jacket. It reduces tripping hazards and lowers impact force from dropped tools. Available in various lengths from 300mm to 1000mm. For direct tool attachment with connectors. Configured with 'D' rings at both ends or with choice of loop design at one end for a greater tool connection ie choking, looping, or with swivel connector one end to prevent twisting. Rated for hand tools up to 5kg.



## Webbing Tool Lanyards

Webbing tool lanyards provide a safe way to secure tools that are lightweight and versatile. Its flat construction style also makes it easy to use in some applications where other types of tool lanyards are unsuitable. The webbing is made of high-strength polyester. This material is strong and flexible, and is resistant to moisture, electrical conductivity and extreme temperature changes. Available in various lengths from 100mm to 1000mm configured with 'D' rings at both ends or with choice of loop design at one end for a greater tool connection ie choking, looping, or with swivel connector one end to prevent twisting. Rated for hand tools up to 5kg.



## Wire Tool Lanyards

Basic lanyard that is strong and reliable. Can be used with both heavy and lightweight tools, it can be attached to a tool belt, holster, harness or scaffold, and it can be attached to various tools in a number of ways. Wire design developed for extreme heavy industrial use in harsh environments. Available with wire loop both ends or with swivel connector one end to prevent twisting. Available in various lengths from 100mm to 1000mm. Rated for hand tools up to 5kg.



Each lanyard has a unique sealed serial number label for your control and inspection.