

33kV Earthing Sets

The standard 33kV Earthing Set is supplied with parking bar, 3 x S9B conductor clamps with taper operating screw (ring type as alternative), 2 x 3 metre 120mm² Aluflex phase leads, 1 x 15 metre 50mm² Aluflex earth lead and 1 x earth end clamp. Clamps are tested to 17.5kA for 2 seconds.

CAT NO	DESCRIPTION
33-EARTH-TS-PB	Standard kit with taper screw clamps
33-EARTH-RC-PB	As above but with ring type clamps
33-EARTH-TS-PB-CN	As 33-EARTH-TS-PB but with 3m crossarm bond lead with CE10 clamp attached
33-EARTH-TS-PB-CN-A	As 33-EARTH-TS-PB but with separate 6m bond lead (CBL-6M-2X-S9AH) with S9AH clamps each end
33-EARTH-RC-PB-CN-A	As 33-EARTH-RC-PB but with separate 6m bond lead (CBL-6M-2X-S9AH) with S9AH clamps each end

Standard 33kV Earthing Set 33-EARTH-RC-PB



33-EARTH-TS-PB



33-EARTH-TS-PB-CN

Standard set plus 3m Crossarm Bond Lead



33kV Earthing Set with 6m Bond Lead



33-EARTH-TS-PB-CN-A



33-EARTH-RC-PB-CN-A

