

Crossarm Clamp

CAT NO: CE10

For direct connection to tower steelwork or crossarm angle. Large 'T' bar has a captive hardened steel tip to penetrate through painted weathered or non-conductive surfaces and indents into steelwork ensuring a strong efficient earth connection.



Alternative Crossarm Clamp

CAT NO: CE29

Alternative Crossarm Clamp, can be attached to angle or tie straps.

Line End Clamp with Long Taper Screw

CAT NO: S9B-LT

Line end clamp manufactured from aluminium alloy and suitable for a conductor range of 3 - 27mm diameter. Designed to make positive connection on to the conductor. Used with HOR-P331 operating socket.



Line End Clamp with Short Taper Screw

CAT NO: S9B-ST

Line end clamp manufactured from aluminium alloy and suitable for a conductor range of 3 - 27mm diameter. Designed to make positive connection on to the conductor. Used with HOR-P331 operating socket.

Line End Clamp - Ring Type

CAT NO: S9B-R

Line end clamp manufactured from aluminium alloy and suitable for a conductor range of 3 - 27mm diameter. Clamps have ring fitting. Used with FA-3215-B-4927 operating head or shotgun stick.



Line End Clamp - Snap On Type

CAT NO: CE-62

Spring loaded snap-on clamp for use on 11kV portable earth sets. Manufactured from aluminium alloy. Used with HOR-DA1 pole head.

Earth End Clamp with Knurled Handle

CAT NO: S9-AH

Fits onto flat bar up to 12.7mm and conductors or earth rods 6.4 to 20mm diameter.

