



CM-410



The CM-410 clamp meter features a narrow, compact design for measuring in tight spaces. Jaw opening 27mm, measurement of resistances up to 20M Ω , data hold function for recording important measurement results, automatic device shut-off, continuity test. Supplied with test leads, durable carry case and 2 x 1.5V AAA batteries.

CAT NO	ACCURACY	DISPLAY	VOLTAGE MEASUREMENT	CURRENT MEASUREMENT	RESISTANCE	MEASUREMENT CATEGORY	JAW OPENING
CM-410	0,7	3 1/2-character LCD (display range 2000)	<600V AC/DC	<400A AC, <600A DC	<20M Ω	CAT III, 600V	27mm

CM-950

The CM-950 clamp meter features true RMS for the most precise measurements if harmonic oscillation is present. Jaw opening of 35mm. Current measurement AC/DC, alternating voltage, frequency and resistance, dual reverberation sensor, backlit display, Peak Hold and Data Hold function, MIN/MAX function, analogue bar chart, automatic zero-point setting, automatic shut-off. Supplied with durable carry case & battery 9V, TSG-3, test leads.



CAT NO	DISPLAY	VOLTAGE MEASUREMENT	CURRENT MEASUREMENT	RESISTANCE	FREQUENCY	MEASUREMENT CATEGORY	JAW OPENING
CM-950	LCD (display range 4000)	<600V AC/DC	<600A	<400 Ω	0.400kHz	CAT III, 600V	35mm



CM-1550

The CM-1550 clamp meter features true RMS for the most precise measurements if harmonic oscillation is present. Jaw opening 51 mm. Current measurement AC/DC, alternating voltage, frequency and resistance, dual reverberation sensor, backlit display, Peak Hold and Data Hold function, MIN/MAX function, analogue bar chart for checking fast changes, acoustic continuity check. Supplied with durable carry case, battery 9V, TSG-3, test leads.

CAT NO	DISPLAY	VOLTAGE MEASUREMENT	CURRENT MEASUREMENT	RESISTANCE	FREQUENCY	MEASUREMENT CATEGORY	JAW OPENING
CM-1550	LCD (display range 4000)	<1,000V AC/DC	<1,000A	<400 Ω	0.400kHz	CAT III 750V AC/ 100V DC, CAT IV 600V	51 mm

CSJ-100

The CSJ-100 is an open jaw type meter for current measurement AC/DC, voltage, frequency and resistance up to 20M Ω , acoustic continuity test and diode test, alarm and LED for contactless voltage detection, automatic shut-off, Data Hold for recording the measured values, 3 1/2-place LCD display (counter value with maximum 1999 points). Supplied with durable carry case, 2 x 1.5V AAA batteries, test leads fixed to the device.



CAT NO	DISPLAY	VOLTAGE MEASUREMENT	CURRENT MEASUREMENT	RESISTANCE	MEASUREMENT CATEGORY	JAW OPENING
CSJ-100	LCD (display range 2000)	<1,000V AC/DC	<200A AC	<20M Ω	CAT II 1000V, CAT IV 600V	16mm



TSGF Fused Test Leads

Measuring cable set with fuses CAT IV 1000V. Suitable for Greenlee clamp meters and digital multimeters. Features double insulated silicone conductors with two coatings, superfine stranded copper cable, highly flexible 1.2 metre cable.