

Borderguard

The Borderguard is designed to protect the exterior of a building or fence. Borderguard is a PIR (passive infrared motion detector) which detects the heat energy emitted by humans. The detector utilises dual beams that project 12m (40') from each side of the unit and is best mounted at a height of 90cm - 120cm (36" - 48"). Both beams must be blocked at the same time to activate the detector. This feature eliminates the potential of false alarms caused by animals in the outdoor environment.



Outdoor Motion Detector



The high powered motion detector is used in cases where you need a stronger signal between the accessory and the TattleTale™ unit. The dual-detection outdoor motion detector can be placed up to 600m (2000') from the TattleTale™ unit depending on structures and objects in between the detector and the TattleTale™. It is sensitive to moving heat (infrared radiation) and has an adjustable coverage area. The maximum coverage area is 12m (40') in a 90° arc.

Rattler

The Rattler can be placed up to 600m (2000') away from the TattleTale™ base unit depending on the objects and structures between the Rattler and the base unit. The Rattler is sensitive to movement and vibration. The Rattler unit can be placed on top of the item(s) to be protected. It can also be attached to any metal object with the integrated magnets. Ideal for protecting vehicles, plant and machinery.



The Loop



The LOOP is a sensor device that can be used indoors and outdoors, ideal for drums of conductor. You can think of it as an electronic bike lock that you can use to tie up your tools and equipment (such as backhoes, generators, ladders, etc). If the LOOP is cut or disconnected when the TattleTale™ alarm unit is armed, an instant alarm signal will be transmitted. The LOOP can be placed up to 600m (2000') away from the alarm unit. Standard cable lengths of 3m (10') and 6m (20'), other lengths available upon request.

High Mount Borderguard

The dual-detection high mount Borderguard motion detector can be placed up to 600m (2000') away from the TattleTale™ alarm unit depending on objects and structures between the detector and the TattleTale™. It is sensitive to moving heat (infrared radiation) and has an adjustable coverage area. The maximum coverage area is 24m (80') long x 1.8m (6') wide, mounted between 2.4m (8') - 3m (10') off the ground.



High Mount Outdoor Motion Detector

The dual-detection high mount outdoor motion detector can be placed up to 600m (2000') away from the TattleTale™ alarm unit depending on objects and structures between the detector and the TattleTale™. It is sensitive to moving heat (infrared radiation) and has an adjustable coverage area. The maximum coverage area is 12m (40') in a 90° arc mounted between 2.4m (8') - 3m (10') off the ground.

Wireless Signal Booster

Double the range of your wireless protection! The signal booster is used to increase the range of the wireless accessories. Use multiple signal boosters to create a super long range wireless security network.



External Siren & Strobe

The remote siren & strobe allows you to place the warning right where you want it. Direct police anywhere on your site to shorten response time. This accessory is triggered when the TattleTale's siren and strobe go off.

