

Hi-Tool Conductor Grips are the lightest and most versatile grips available. These grips are designed for and tested on a very wide range of conductors which will, in many cases, allow the replacement of 3 traditional grips with a single Hi-Tool model. The consequent benefits in cost, space and weight saving are considerable.

Further, a patented "One Hand Trigger Grip Operation" allows the tool to easily be placed on to the conductor. Each grip comes with a gate designed to help guide it along the conductor during installation. However for those users who prefer a grip without this feature the gate can be stowed in the open position, or removed completely, without affecting the performance of the grip. Where required a fully hot-stick enabled grip is available.

Grips for larger conductors have a patented twist grip handle which allows better alignment of the ratchet puller and grip reducing the possibility of distortion and damage to the conductor.

Our standard range includes grips for all sizes of copper, aluminium and ACSR conductors with specialist grips available for covered conductor, such as BLL, Stay wire, and ABC conductors.

All grips are CE marked and supplied with a declaration of conformity from the manufacturer.

## Bare Al, Cu & ACSR Grip

A versatile, lightweight grip for bare Cu, Al & ACSR.

**HT-1** - this one grip can replace three grips from other manufacturers.

**HT-3** - for larger conductors, this grip covers a wide conductor range whilst being significantly lighter than the competition.

CAT NO	CONDUCTORS	WLL	WEIGHT
HT-1	25mm <sup>2</sup> to 100mm <sup>2</sup> AAAC & ACSR 16mm <sup>2</sup> to 125mm <sup>2</sup> HD Copper	1600kg	1.5kg
HT-3	175mm <sup>2</sup> to 300mm <sup>2</sup> AAAC 150mm <sup>2</sup> to 200mm <sup>2</sup> ACSR	4120kg	4.7kg



## Premium Grip

Combining the extensive range taking capacities of the HT-1 and HT-3 this grip offers an alternative for medium sizes of conductor. Offering a longer jaw length than the HT-1 with a greater working load limit.

CAT NO	CONDUCTORS	WLL	WEIGHT
HT-1M	50mm <sup>2</sup> to 175mm <sup>2</sup> AAAC 50mm <sup>2</sup> to 175mm <sup>2</sup> ACSR 32mm <sup>2</sup> to 150mm <sup>2</sup> HD Copper	2000kg	1.9kg



## Staywire Grip

Easy to apply, lightweight grip for standard staywire range.

CAT NO	STAYWIRE	WLL	WEIGHT
HT - STAY	7/3.25mm & 7/4mm	2245kg	1.7kg

**Please contact us for further information on grips for specific conductors**