

New Orange Line series of 10.8V Mini Light Insulated Crimping and Cutting Tools are ideal for linesmen and jointers. Combining many of the features and capacity of the 18V models in a more compact and lightweight tool. This range is more cost effective due to slightly reduced digital functionality. All tools utilise standard DeWalt 10.8V Batteries and Chargers which are sold separately.

New Mini Light W Die Crimp Tool is ideal for linesmen, combining many of the features and capacity of the 18V model in a more compact and lighter weight tool.

- Fully insulated to the electrical requirements of IEC 60900
- More cost effective model due to slightly reduced functionality
- Takes standard 10.8V DeWalt Li-Ion Batteries

Klauke EK425ISML

Insulated battery powered hydraulic open head 'W' die tool

CAT NO (TOOL ONLY)	EK425ISML
CRIMPING FORCE	15kN
STROKE/OPENING WIDTH	40mm
CRIMP RANGE	Full range of 'W' dies
NUMBER OF CRIMPS	Approx 150 dependent on conductor dia
WEIGHT INC. BATTERY	2.62kg



Klauke ES20ISML

Insulated battery powered hydraulic cutting tool 20mm dia.

CAT NO (TOOL ONLY)	ES20ISML	ES32ISML
CUTTING FORCE	23kN	15kN
CUTTING RANGE	20mm dia	32mm dia
CABLE TYPES	ACSR, Cu, Al	Cu & Al
HEAD TYPE	Open scissor	Open scissor
WEIGHT INC. BATTERY	2.1kg	2.0kg

- Fully insulated to the electrical requirements of IEC 60900
- Compact and lightweight
- Open cutting head rotates infinitely
- Automatic retraction when the operation is complete
- Manual retraction where required



Klauke®

Interchangeable Heads available for EK425ISML



CJ-E

EK425ISM accepts all W Dies except 'WE'. Use CJ-E for 'E' profiled crimps.



CJACSRINS

Cuts up to 20mm dia. ACSR



CJCUINS

Cuts up to 20mm dia. Cu / Al

Klauke ES32ISML



Insulated battery powered hydraulic cutting tool 32mm dia.

Image shown with shrouded head - available for both models. Add suffix -WSH to Cat No

- Environmentally-friendly hydraulic oil, biodegradable
- Quick motor stop
- Ergonomic 2-component housing with soft grips for comfortable and safe, one hand operation
- Multifunction LED for maintenance control and analysis of data via optical interface and USB adapter
- Optimal centre of gravity