



Right Angle LED Rechargeable

- Extremely lightweight & fully waterproof to 1m
- Battery charge status indicator
- Slim and compact to keep torch close to your body
- Optional alkaline tray available
- Stainless steel mounting clip



CAT NO	LIGHT OUTPUT	DISTANCE	BATTERY TYPE	RUN TIME	WEIGHT
BS-510221	205 lumens	<477m	Rechargeable / L-Ion	4hr	0.45 kg



Worksafe LED Standard

- Anti-roll tube
- Oversized, faceted reflector for more light
- Fully waterproof to 1m
- Multiple models available, all have three-way switch: on-off-flash

CAT NO	LIGHT OUTPUT	DISTANCE	BATTERY TYPE	RUN TIME	WEIGHT
BS-15460	50 lumens	<88m	2 x D Cell	200hr	0.14 kg
BS-8050	90 lumens	<314m	4 x D Cell	150hr	2.6 kg

Worksafe LED ATEX, Zone 0

- Deep ribbed case, non-slip grip which meets marine standard
- Multiple models available, all waterproof to 1m & have 3-way switch: On-Off-Flash
- Faceted reflector with a lens ring



CAT NO	LIGHT OUTPUT	DISTANCE	BATTERY TYPE	RUN TIME	WEIGHT
BS-16460	50 lumens	<88m	2 x D Cell	200hr	0.14 kg
BS-9050	90 lumens	<165m	4 x D Cell	150hr	2.6 kg



Industrial LED

- Economical and reliable
- Impressive 200hr run time and a 75m beam
- Deep ribbed case for non-slip grip, anti-roll tube

CAT NO	LIGHT OUTPUT	DISTANCE	BATTERY TYPE	RUN TIME	WEIGHT
BS-11500	50 lumens	<75m	2 x D Cell	200hr	0.28 kg